

Datasheet

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

CDD-1 24" Black 2 Tap Refrigerated Direct Draw Beer Dispenser



FEATURES

- · All stainless steel construction
- · Exterior construction vinyl on steel in black finish
- · Holds temperatures between 33°F and 41°F
- · Electronic control system
- · Adjustable heavy-duty PVC coated shelves
- · Self-closing doors with locks
- · LED interior lighting
- Hydro-Carbon R290 refrigerant
- · Removable installation board for easy cleaning

This Coldline beer dispenser is ideal for bars and restaurants that need to store draft beer "on tap." Hold barrels or wall kegs in refrigerated sections, and keep your customer's favorite brew flowing on-demand. Coldline draft beer dispensers are equipped with electronic temperature control to keep the product at the ideal refrigeration point. Interior LED lighting, self-closing doors, and adjustable PVC shelves all make this unit a reliable commercial refrigerated beer dispenser for any bar service.

- cETLus Listed
- ETL Sanitation Listed Conforms to UL & NSF Standards





USR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.



Datasheet

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

TECHNICAL DATA

DIMENSIONS

DIMENSIONS	
Exterior Dimensions	23.5"W x 30.4"D x 38.75"H
Interior Dimensions	19.5"W x 18"D x 28.6"H
Packaging Dimensions	26"W x 32.25"D x 45"H
Faucet Height	10"H
Tap Tower Dimensions	16"H 3" Diameter
Working Height	35.3"
Net Volume	6.5 cu. ft.
Unit Weight	132 lb.
Shipping Weight	176 lb.

FI FCTRICAL

LLLCTITICAL	
Voltage	115
Hertz	60
Phase	1
Amps	1.92
Plug Type	NEMA 5-15P
Horsepower	1/6
Power Cord Length	84"

COOLING

Temperature Range	33°F ~ 41°F
Temperature Controller	Digital
Refrigerant	R-290 (Hydro-Carbon)
Max Ambient Temp	90°F
Defrost	Automatic

CONSTRUCTION

201101110211011	
Exterior Material	430 Series Stainless Steel
Interior Material	304 Series Stainless Steel
Insulation Material	Foamed-In-Place Polyurethane
Number of Taps	2
Number of Doors	1
Shelf Material	Epoxy Coated Steel
Shelf Load	90 lb.

TECHNICAL DRAWING

MODEL: CDD-1

MFR ITEM #:







