

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

D12-W 27" White Single Glass Swing Door Merchandiser Freezer



FEATURES

- White coated exterior
- Attractive aluminum liner with stainless steel floor
- Refrigeration system keeps food at safe temperatures
- Self-closing doors with 90 degree stay-open feature
- Adjustable heavy-duty PVC coated shelves
- Pull out door handle
- Electronic control system
- Preinstalled heavy-duty casters with brakes
- Removable installation board
- Hydro-Carbon R290 refrigerant

This Coldline commercial glass door merchandiser freezer is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

- cETLus Listed
 - ETL Sanitation Listed
- Conforms to UL & NSF Standards



USR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	27.2"W x 26.2"D x 83.7"H
Interior Dimensions	21.3"W x 19.3"D x 59.7"H
Packaging Dimensions	29.5"W x 30"D x 85"H
Net Volume	12.89 cu. ft.
Unit Weight	304 lb.
Shipping Weight	348 lb.

ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	5.18
Plug Type	NEMA 5-15P
Power Cord Length	84"

COOLING

Temperature Range	-10°F to 0°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	5/6

CONSTRUCTION

Exterior Material	Coated Steel
Exterior Color	White
Interior Material	White Aluminum and Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Door Style	Swing
Door Type	Glass
Shelf Size	(4) 20.9"W x 17.3"D
Shelf Load Capacity	90 lb.
Shelf Material	Epoxy Coated Steel
Adjustable Shelf	Yes
Interior Light	L.E.D
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

TECHNICAL DRAWING

MODEL: D12-W

MFR ITEM #:



NEMA 5-15P

