

G40-B 48" Black Double Glass Swing Door Merchandiser Refrigerator



FEATURES

- ▶ Black coated exterior
- ▶ Attractive aluminum liner with stainless steel floor
- ▶ Refrigeration system keeps food at safe temperatures
- ▶ Self-closing doors with 90 degree stay-open feature
- ▶ Adjustable heavy-duty PVC coated shelves
- ▶ Pull out door handle
- ▶ Electronic control system
- ▶ Preinstalled heavy-duty casters with brakes
- ▶ Removable installation board
- ▶ Hydro-Carbon R290 refrigerant

This Coldline commercial glass door merchandiser refrigerator is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

- ▶ cETLus Listed
 - ▶ ETL Sanitation Listed
- Conforms to UL & NSF Standards



US Restaurant Group is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.



Datasheet

Project:**Quantity:****Model #:****Approval:***For Commercial Use Only*

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	48"W x 25.6"D x 82.75"H
Interior Dimensions	43"W x 19"D x 55"H
Packaging Dimensions	50.8"W x 29.5"D x 87"H
Net Volume	29 cu. ft.
Unit Weight	375 lb.
Shipping Weight	418 lb.

ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	3
Plug Type	NEMA 5-15P
Power Cord Length	84"

COOLING

Temperature Range	33°F to 41°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/4+

CONSTRUCTION

Exterior Material	Coated Steel
Exterior Color	Black
Interior Material	White Aluminum and Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Door Style	Swing
Door Type	Glass
Shelf Size	(8) 18.8"W x 24.3"D
Shelf Load Capacity	90 lb.
Shelf Material	Epoxy Coated Steel
Adjustable Shelf	Yes
Interior Light	L.E.D
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

DIAGRAM

MODEL:G40-B

MFR MODEL:G768BM2F-HC



NEMA 5-15P

