

## M56R 54" Double Solid Door Top Mounted Reach-In Refrigerator



### FEATURES

- ▶ Top mounted compressor
- ▶ Stainless steel interior and exterior
- ▶ Galvanized steel back
- ▶ CFC free refrigerant and foam
- ▶ Self-closing door with heavy duty pull handle
- ▶ Adjustable heavy-duty PE coated shelves
- ▶ Rounded interior corners for easy cleaning
- ▶ Standard heavy-duty casters
- ▶ Refrigeration system hold 33°F to 41°F temperature
- ▶ Preinstalled heavy-duty casters with brakes
- ▶ L.E.D light for bright illumination
- ▶ Hydro-Carbon R290 refrigerant

This Coldline stainless steel reach-in commercial refrigerator is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

- ▶ cETLus Listed
- ▶ ETL Sanitation Listed
- ▶ NSF Compliant



### WARRANTY

Coldline products are backed by a 1 Year / 5 Year limited manufacturer warranty. The unit itself and parts within are guaranteed against manufacturing defects for a period of 1 year. The compressor is guaranteed for an additional 4 years. Extended warranty is available. Glass, due to its fragile nature, is not included under warranty coverage. Always inspect your delivery for freight damage before you accept it. Freight damage will not be considered a manufacturing defect and should be refused or remedied through a claim with the carrier.



## TECHNICAL DATA

### DIMENSIONS

Exterior Dimensions	53.9"W x 32.8"D x 82.8"H
Packaging Dimensions	55.3"W x 34"D x 83"H
Net Volume	45 cu. ft.
Unit Weight	170 lb.
Shipping Weight	193 lb.

### ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	2.5
Plug Type	NEMA 5-15P
Power Cord Length	3'

### COOLING

Temperature Range	33°F to 41°F
Refrigerant	R290
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/4+

### CONSTRUCTION

Exterior Material	Stainless Steel
Interior Material	Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Shelf	3
Shelf Material	PE Coated Wire
Shelf Load Capacity	120 lb.
Adjustable Shelf	Yes
Interior Light	L.E.D
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

## DIAGRAM

### MODEL: M56R

MFR MODEL: M56R

