

Datasheet

| Project: | Quantity: |
|----------|-----------|
| Model #: | Approval: |

For Commercial Use Only

UDD-24-24 24" Black 2 Tap Refrigerated Direct Draw Beer Dispenser



FEATURES

- ▶ All stainless steel construction
- Exterior construction vinyl on steel in black finish
- ▶ Holds temperatures between 33°F and 41°F
- ▶ Electronic control system
- ▶ Adjustable heavy-duty PVC coated shelves
- ▶ Self-closing doors with locks
- ▶ LED interior lighting
- ▶ Hydro-Carbon R290 refrigerant
- ▶ Removable installation board for easy cleaning

This Coldline beer dispenser is ideal for bars and restaurants that need to store draft beer "on tap." Hold barrels or wall kegs in refrigerated sections, and keep your customer's favorite brew flowing on-demand. Coldline draft beer dispensers are equipped with electronic temperature control to keep the product at the ideal refrigeration point. Interior LED lighting, self-closing doors, and adjustable PVC shelves all make this unit a reliable commercial refrigerated beer dispenser for any bar service.

- cETLus Listed
- ETL Sanitation Listed





S Restaurant Group is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.



Datasheet

| Project: | Quantity: |
|----------|-----------|
| Model #: | Approval: |

For Commercial Use Only

TECHNICAL DATA

DIMENSIONS

| DIMENSIONS | |
|----------------------|---------------------------|
| Exterior Dimensions | 23.5"W x 30.4"D x 38.75"H |
| Interior Dimensions | 19.5"W x 18"D x 28.6"H |
| Packaging Dimensions | 26"W x 32.25"D x 45"H |
| Faucet Height | 10"H |
| Tap Tower Dimensions | 16"H 3" Diameter |
| Working Height | 35.3" |
| Net Volume | 6.5 cu. ft. |
| Unit Weight | 132 lb. |
| Shipping Weight | 176 lb. |

ELECTRICAL

| Voltage | 115 |
|-------------------|------------|
| Hertz | 60 |
| Phase | 1 |
| Amps | 1.92 |
| Plug Type | NEMA 5-15P |
| Horsepower | 1/6 |
| Power Cord Length | 84" |

COOLING

| Temperature Range | 33°F ~ 41°F |
|------------------------|----------------------|
| Temperature Controller | Digital |
| Refrigerant | R-290 (Hydro-Carbon) |
| Max Ambient Temp | 90°F |
| Defrost | Automatic |

CONSTRUCTION

| Exterior Material | 430 Series Stainless Steel |
|---------------------|------------------------------|
| Interior Material | 304 Series Stainless Steel |
| Insulation Material | Foamed-In-Place Polyurethane |
| Number of Taps | 2 |
| Number of Doors | 1 |
| Shelf Material | Epoxy Coated Steel |
| Shelf Load | 90 lb. |

DIAGRAM

MODEL:UDD-24-24

MFR MODEL: UDD-1-HC







