

Datasheet

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

XS205 35" Flat Glass Top Display Ice Cream Freezer



FEATURES

- ▶ Holds Temperature Between -13°F To 0°F
- ▶ Flat Glass Top Lid With Sliding Doors
- ▶ White Powder Coated Steel Exterior
- ▶ Embossed Aluminum Interior
- ▶ Preinstalled Low Profile Casters With Brakes
- ▶ Drain Plug For Manual Defrosting
- ▶ Coated Wire Basket Included
- ▶ R134a Refrigerant

This heavy duty ice cream freezer is designed to help increase impulse sales in your cafe, bakery, convenience store, diner, or market spot. A clear flat glass top, embossed aluminum interior, optimal temperature management, and an overall durable design helps make Coldline the perfect choice for commercial applications. Entice customers to frozen treats popsicles, pizzas, desserts, etc - and maximize your sales. The white-coated, sleek steel exterior adds a sense of cleanliness and enriches your food spaces.

- ▶ ETL Certified
- ▶ ETL Sanitation
- ▶ NSF Compliant







WARRANTY

Coldline products are backed by a 1 Year / 5 Year limited manufacturer warranty. The unit itself and parts within are guaranteed against manufacturing defects for a period of 1 year. The compressor is guaranteed for an additional

4 years. Extended warranty is available. Glass, due to its fragile nature, is not included under warranty coverage. Always inspect your delivery for freight damage before you accept it. Freight damage will not be considered a manufacturing defect and should be refused or remedied through a claim with the carrier.





US Restaurant Group, Inc.

Rev. 9-2018

Phone: 800-764-1172 | www.usrestaurant.com | sales@usrestaurant.com



Datasheet

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

(o ` [[

NEMA 5-15P

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	35.4"L x 21.9"D x 32.7"H
Interior Dimensions	30"L x 17"D x 25"H
Packaging Dimensions	36.75"L x 23.75"D x 34.25"H
Net Volume	6 cu. ft.
Unit Weight	80 lb.
Shipping Weight	90 lb.

ELECTRICAL

Voltage	110
Hertz	60
Phase	1
Amps	2.3
Kilowatt-Hour	1.527
Plug Type	NEMA 5-15P
Power Cord Length	72"

COOLING

Temperature Range	-13°F - 0°F
Refrigerant	R134a
Max. Ambient Temp	90°F
Defrosting	Manual
Temperature Controller	Manual
Horsepower	1/6

CONSTRUCTION

Exterior Material	White Powder Coated Steel
Interior Material	Embossed Aluminum
Insulation Material	Foamed-in-Place Polyurethane
Basket	1 Qty: 20.2"L x 9.5"D x 11"H
Basket Material	Coated Wire
Drain Plug Location	Back Side

DIAGRAM



MFR MODEL:





