# marchia

# **Datasheet**

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

# MDS250 24" Open Air Cooler Grab & Go Display Refrigerator



### **FEATURES**

- · Brilliant Internal LED lighting on top and bottom
- · Digital temperature controller and display
- (4) Casters with (2) brakes
- · Double tempered glass
- With night curtain
- · Ventilated cooling system
- · Automatic defrost
- · Filter mesh in front of the base
- · Adjustable shelves
- · Condensator at back side free of maintenance
- · Condensation water evaporated automatically

This Marchia refrigerated open grab and go food display case includes LED lighting and adjustable shelves as well a user accessible digital temperature controller. Open display to provide customer with access.

- cETLus Listed
- ETL Sanitation Listed

Conforms to UL & NSF Standard



USR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.

# marchia Datasheet

Project:	Quantity:	
Model #:	Approval:	

For Commercial Use Only

# **TECHNICAL DATA**

#### **DIMENSIONS**

Exterior Dimensions	24"L x 29.6"D x 67"H
Packaging Dimensions	26.7"L x 32.4"D x 74.4"H
Net Volume	9 cu. ft.
Unit Weight	221 lb.
Shipping Weight	276 lb.

#### **ELECTRICAL**

Voltage	110-120
Hertz	60
Phase	1
Wattage	1220
Amps	11.8
Plug Type	NEMA 5-15P
Power Cord Length	79"

### COOLING

- CO 0 2 1 C		
Temperature Range	36°F to 50°F	
Refrigerant	R290	
Defrosting	Automatic	
Temperature Controller	Digital	

#### **CONSTRUCTION**

Exterior Material	Glass and Stainless Steel
Shelf Quantity	3 + Base
Shelf Size	Top: 21.2"L x 10.8"D Middle: 21.2"L x 13.6"D Bottom: 21.2"L x 13.6"D
Shelf Material	Coated Wire
Adjustable Shelf	Yes
Interior Light	(4) L.E.D
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

# **TECHNICAL DRAWING**

MODEL: MDS250

MFR ITEM #:




**NEMA 5-15P** 


FRONT VIEW



SIDE VIEW



BACK VIEW



• Designed to operate in locations not exceeding 75°F and 55% relative humidity.

**USR** = USR Brands, Inc.

Rev. 08-2024 **Page 154**